

Dräger Interlock XT



ST 1659-1003

The Dräger Interlock XT is a breath-alcohol measuring instrument with a vehicle immobilizer. After taking a breath alcohol measurement, it prohibits a driver who has consumed alcohol from starting the motor. It can easily be installed into the vehicle. By installing a Dräger Interlock XT, you can avoid accidents caused by alcohol consumption. Additionally, long-term changes in the drinking attitude may be an added benefit.



ST-162-2005

Dräger Interlock XT:
A safe start

Components

The Dräger Interlock XT comprises two main components: the breath-alcohol measuring instrument with the measuring system, which is situated inside the vehicle, and the control unit which is generally installed under the dashboard and allows or prevents current being supplied to the vehicle's starter system.

Operation

When the ignition is switched on, the Dräger Interlock XT requests a breath sample from the driver. The result of the breath-alcohol concentration measurement determines whether the vehicle's starter is released and the engine can be started.

Application

Car drivers find long waits after switching on the ignition particularly annoying. Therefore, during development of the Dräger Interlock XT, particular attention was paid to ensuring that the instrument would be ready for use quickly.

Because the Dräger Interlock XT even works perfectly at -40°C (during the Scandinavian winter, for example) and at 85°C (in blazing sunlight, for example), it was given the name "XT", for "eXtended Temperature".

Measuring technique

The Dräger Interlock XT determines the breath alcohol concentration by means of an electrochemical sensor system, as it is used also in breath-alcohol measuring instruments of police authorities. It reacts with high specificity to alcohol. As a result, other exhaled substances or cigarette smoke do not distort the measurement result.

Data storage

While the vehicle is in use, all relevant events are recorded in the Dräger Interlock XT's data log: date, time, submission of or refusal to submit a breath sample, measured alcohol concentration, engine starts and stops, electrical bypassing of the Interlock and any other attempts to tamper with the device. The data can be downloaded and compiled in a data record.

Manipulation

The use of auxiliary means to circumvent the Dräger Interlock XT, as for example an air pump or the use of filters, is reliably detected and starting the motor is prevented. A vehicle start-up as by push-start without previous delivery of an accepted breath sample is recorded in the data log.

Properties of the Dräger Interlock XT:

- Prevents the starting of the vehicle when alcohol is detected in the driver's breath
- Leads to immediate separation of alcohol intake and driving
- Prevents accidents while under the influence of alcohol
- Is resistant to tampering
- Offers the possibility for cyclic retests
- Records all events in data storage for later review
- Increases safety for drivers and passengers
- Can improve the image of transport companies
- Supports long-term attitude changes towards overcoming alcohol problems

Handset

Is situated in the passenger compartment

Mouthpiece

With hygienic non-return valve

Display

User guidance by text messages

Control unit

Is installed under the dashboard


Cabels

Connection to the vehicle's electrics



ST-1023-2003

1. Turn ignition on




ST-1865-2006

2. Receive request to blow into Dräger Interlock XT



ST-1667-2003

3. Measurement of breath-alcohol concentration takes place



ST-187-2005

4. Accepted breath sample: motor starter is enabled



ST-1924-2003

5. Start motor

Breath alcohol measurement

Dräger is world market leader in breath alcohol measurement. The Alcotest® family of products is the most successful breath-alcohol measuring instrument world-wide.

The well known Alcotest tube with the sample bag is probably the oldest method of obtaining proof of alcohol consumption. Today, most alcohol detection devices are electronic.

They are used on all five continents for traffic safety by police authorities, for workplace alcohol testing, as well as aiding in the diagnosis of medical patients.

Dräger's long term experience and time proven measuring technique establishes the basis of the Dräger Interlock XT.

TECHNICAL DATA

Measuring principle	Electrochemical sensor	
Ambient conditions for operation	Temperature	-40 to 85 °C (-40 to 185°F)
	Pressure	600 to 1100 hPa
	No influence of changes in altitude on the measurement result	
Sensitivity drift	typically 1 % of measured value / month	
Ready for test	< 20 sec. (above 20°C / 68°F)	
	< 3 min. (at -40°C / -40°F)	
Display	graphic LC-display in the handset with full text messages	
Calibration interval	typically 6 months	
Data memory	in handset, for more than 30.000 events	
Dimensions (H x W x D)	Handset	approx. 150 mm x 70 mm x 40 mm
	Control unit	approx. 115 mm x 105 mm x 40 mm
Weight	Handset	approx. 175 g
	Control unit	approx. 320 g
Voltage supply	12 V	
	Starter relay may switch up to 48 V; 12 V subnet for instrument supply necessary	
Relay for the lead starter relay	< 16 A, continuous	
	< 40 A, peak	
Current consumption	< 2 A; maximum	
	< 20 mA; stand-by	
Approvals	Radio interference	
	(Directive 95/54/EC and ECE Regulation No.10)	
	General German Operating Permission	
	(Allgemeine Betriebserlaubnis)	



ST-1668-2003

Dräger Interlock XT:
Use in carrying business.



ST-1670-2003

Dräger Interlock XT:
Fits in the dashboard.




ST-1674-2003

Dräger Interlock XT:
Use in private car.

ORDER INFORMATION

Dräger Interlock XT	83 16 200
Breath-alcohol controlled vehicle immobilizer (handset and control unit) for installation in motor vehicles, mouthpieces (5 pieces) and mounting accessories	
Mouthpieces (5 pieces) separately packed	68 10 478



SUBSIDIARIES

AUSTRALIA

Draeger Safety Pacific Pty. Ltd.
Axxess Corporate Park
Mt. Waverley. Vic 3149
Tel +61 3 92 65 50 00
Fax +61 3 92 65 50 95

CANADA

Draeger Canada Ltd.
7555 Danbro Crescent
Mississauga, Ontario L5N 6P9
Tel +1 905 821 8988
Fax +1 905 821 2565

P. R. CHINA

Beijing Fortune Draeger
Safety Equipment Co., Ltd.
Beijing 101300
Tel +86 10 80 49 80 00
Fax +86 10 80 49 80 05

FRANCE

Dräger Safety France S.A.S.
3c, Route de la Fédération
67025 Strasbourg Cedex
Tel +33 388 40 76 76
Fax +33 388 40 76 67

MEXICO

Draeger Safety S.A. de C.V.
Av. Peñuelas No. 5
Querétaro, Oro México
Tel +52 442 246 1113
Fax +52 442 246 1114

NETHERLANDS

Dräger Safety Nederland B.V.
Edisonstraat 53
2700 AH Zoetermeer
Tel +31 79 344 46 66
Fax +31 79 344 47 90

SINGAPORE

Draeger Safety Asia Pte. Ltd.
67 Ayer Rajah Crescent # 06 03
139950 Singapore
Tel +65 68 72 92 88
Fax +65 67 73 20 33

REP. OF SOUTH AFRICA

Dräger South Africa (Pty) Ltd.
P.O.Box 68601
Bryanston 2021
Tel +27 11 465 99 59
Fax +27 11 465 69 53

SPAIN

Draeger Safety Hispania S.A.
Calle Xaudaró 5
28034 Madrid
Tel +34 91 728 34 00
Fax +34 91 729 48 99

UNITED KINGDOM

Draeger Safety UK Ltd.
Kitty Brewster Industrial Estate
Blyth, Northumberland NE24 4RG
Tel +44 1670 352 891
Fax +44 1670 356 266

USA

Draeger Safety, Inc.
101 Technology Drive
Pittsburgh, PA 15275
Tel +1 412 787 8383
Fax +1 412 787 2207

Dräger Safety AG & Co. KGaA

Revalstrasse 1
23560 Luebeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
www.draeger-safety.com